

DIN Standard Schedule 80 Seamless Stainless Steel Tubing TP321 / 904I 347

Basic Information

Place of Origin: CHINA
Brand Name: zheheng
Certification: ISO9001 PED
Model Number: 1"*sch10s
Minimum Order Quantity: Negotiable
Price: Negotiable

Packaging Details: In bundles with waterproof material,or

wooden crate packing

• Delivery Time: 30 DAYS

Payment Terms: L/C, T/T, D/A, D/PSupply Ability: 50TONS/30DAYS



Product Specification

Material: TP321/904I/347
Standard: ASTM ,EN,DIN
Type: Seamless
Technique: Cold Rolling
Outer Diameter: 6mm-630mm
Surface: Bright Annealing
Highlight: ss seamless tube,

ss seamless tube, 304 stainless steel seamless pipe



Product Description

DIN Standard Schedule 80 Seamless Stainless Steel Tubing TP321 / 904I 347

zheheng steel is one of manufacturer ,exporter, stockholder ,supplier of ASTM ,EN,DIN standard Schedule 20/40/80/120/160 seamless stainless steel tubing TP321/904l/347 products,

Products description:

Nominal Dia: 1/2 "to 32" NB for seamless stainless steel tubing

Schedules: 5S, 10S, 40S, 80S, 10, 20, 30...120, 140, 160, XXS All dimensions are in accordance with ANSI B36.19 and ANSI B36.10

Size Range for tubing: OD:1/4" (6.25mm) to 8" (203mm), WT 0.02" (0.5mm) to 0.5"(12mm)

Length:30 m(Max) or as your requirement

Process: Cold drawn, Cold rolled, Precision Rolled for Seamless Pipe or Tube

Finish: Annealed & pickled, bright annealing, polished

Ends: Beveled or plain end, square cut, burr free ,Plastic Cap at Both end

Packing: Bare packing/bundle packing with woven bag/wooden or steel frame crate packing/plastic cap protection at the both sides of tubes and suitably protected for sea-worthly delivery or as requested.

Application:

Seamless stainless steel tubing cold drawn and hot rolled, used in fluid Transportation, construction and other general applications.

ASTM A312, ASTM A213, ASTM A269, ASTM A511, JIS349, DIN17456, ASTM A789, ASTM A790, DIN17456, DIN17458, EN10216-5, JIS3459, GOST 9941-81

Material Grade:

304, 304L, 316, 316L, 321, 321H, 310S, 347H,309.317.0cr18N9, 0Cr25Ni20 ,S31803,S31500,S32750

Size:

Outer Diameter: 6mm to 710mm Thickness: 0.6mm - 48mm

Size:

OD (6-710) x (0.9-40) x MAX 13000mm

Surface:

180G, 320G Satin / Hairline (Matt Finish, Brush, Dull Finish

Duplex and Others:

S32750 ,S32760 , UNS S32304, UNS S32205, UNS S31803, UNS 32160, UNS S32101

Size:

OD:1/4" (6.25mm) to 8" (203mm), WT: 0.02" (0.5mm) to 0.5"(12mm) Length:5.8m, 6m, 11.8m, 12m, 30m(Max) or as your requirement

Process: Cold drawn, Cold rolled, Precision Rolled for Seamless Pipe or Tube Ends: Beveled or plain end, square cut, burr free ,Plastic Cap at Both end

Product Description

Standard & Tolerance: ASTM A213,ASTM A269,EN10216-5 TC1,D4/T3

NDT: Eddy Current or Hydraulic Test Heat Treatment: Bright Annealed

3.1Chemical Composition:3. Material2.Description:

Grade	С	Si	Mn	Р	S	Ni	Cr	Мо	N
409	≤0.08	≤1.0	≤1.0	≤0.04	≤0.03	≤0.5	10.5-11.7		Ti6xC%≤0. 70
409L	≤0.03	≤1.0	≤1.0	≤0.04	≤0.03	0.5	10.5-11.7		Ti8xC%≤0. 70
430	≤0.12	≤1.0	≤1.0	≤0.04	≤0.03		16.0-18.0		
SS329J4L	≤0.03	≤1.0	≤1.5	≤0.04	≤0.03	5.50-7.50	24.00-26.00	2.50- 3.50	
				•		•	•		

3.2 Mechanical Property: Tensil Yield Eloc

Hard

AS TM	Stren	ath	Elog ation (%)	ness (HR B)
40 9	≥380	≥205	≥20	≤80
40 9L	≥350	≥185	≥22	≤80
43)	≥450	≥205	≥22	≤80
SS 32 9J 4L	≥620	≥450	≥18	≤320

production range:

	TP304,TP304L,TP304H,TP304N,
	TP310S,TP316,TP316L,TP316Ti,TP316H,
	TP317,TP317L, TP321, TP321H,TP347, TP347H,904L
Duplex Steel :	S32101,S32205,S31803,S32304,S32750, S32760
	Others:TP405,TP409, TP410, TP430, TP439

Seamless stainless steel tubing U tubings show:





Wenzhou Zheheng Steel Industry Co.,Ltd







e stainless-steelseamlesspipe.com

No999 .wenzhou airport wenzhou city,zhejiang china