


# BW 45 Degree Industrial Steel Pipe Fittings 316 / 316L Thin Wall Sanitary

# **Basic Information**

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- · Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:

- ISO9001 PED 4"\*sch10s
- Negotiable



30 DAYS

CHINA

zheheng



## **Product Specification**

- Standard:
- Packing:

• Type:

ASTM A403 Asme B16.9

wooden crate packing

L/C, T/T, D/A, D/P

100TONS/30DAYS

- Technique:
- Applications:
- Material:
- Highlight:

- Wooden Case,
- 45 Degree
- Butt Welding
- Power, Gas, Metallurgy
  - 4 Way Cross
- stainless steel pipe reducer fittings, stainless steel pipe reducer fittings



**Our Product Introduction** 

## BW 45 degree seamless butt welding stainless steel elbow ASTM A403 pipe fittings

zheheng steel Specialized in supplying BW 45 degree seamless butt welding stainless steel elbow ASTM A403 pipe fittings and offering a wide range of industrial and sanitary quality pipe fitting, quick coupling for wide used in the industries of semi-conductor, petro chemical, Paper & Pulp, Brew, Chemical, Auto&motorcycle, sewage, water and foodbyginic ,Dairy, food, drink, beer, cosmetics, fine chemical etc with many years experience,

#### product details:

Size	1/4"-4" or DN10-DN120
Material	SS304/SS316L
Standard	3A/ISO:9001/CE/TUV
Gasket	Silicone/EPDM/PTFE etc.
Surface Treatment	Polishing/Acid pickling/
Certification	3A/ISO:9001/CE/TUV etc
Application	Dairy, food, drink, beer, cosmetics, fine chemical etc.
Machine Processing	The most advanced CNC machine from Japan for processing
Speial Design	We can produce according to your drawings(Support

### 3.1Chemical Composition:3. Material

Grade	С	Si	Mn	P	S	Ni	Cr	Мо	N
201(1Cr17Mn6Ni5N)	≤0.15	≤1.0	≤5.5	≤0.06	≤0.03	3.5-5.5	16.0-18.0	-	≤0.25
202(1Cr18Mn8Ni5N)	≤0.15	≤0.07	≤7.5	≤0.06	≤0.03	4.0-6.0	17.0-19.0	<b> </b>	≤0.25
304(0Cr18Ni9)	≤0.08	≤0.07	≤2.0	≤0.04	≤0.03	8.0-11.0	18.0-20.0	F	-
304L(00Cr18Ni10)	≤0.03	≤0.07	≤2.0	≤0.04	≤0.03	8.0-11.0	18.0-20.0	F	<u> </u>
305	≤012	≤1.00	≤2.00	≤0.045	≤0.030	10.5-13.0	17.0-19.0		
316(0Cr17Ni12Mo2)	≤0.08	≤0.07	≤2.0	≤0.04	≤0.03	11.0-14.0	16.0-18.0	2.0-3.0	<u> -</u>
316L(0Cr17Ni14Mo2)	≤0.03	≤0.07	≤2.0	≤0.04	≤0.03	11.0-14.0	16.0-18.0	2.0-3.0	-
309s	≤0.08	≤1.00	≤2.0	≤0.045	≤0.03	12.00-15.00	22.00-24.00		
310s	≤0.08	≤1.50	≤2.0	≤0.045	≤0.03	19.00-22.00	24.00-26.00		
3171	≤0.03	≤1.00	≤2.0	≤0.045	≤0.03	11.0-15.0	18.0-20.0	3.0-4.0	
321	≤0.08	≤1.0	≤2.0	≤0.04	≤0.03	9.0-12.0	17.0-19.0		Ti≥5xC
409	≤0.08	≤1.0	≤1.0	≤0.04	≤0.03	≤0.5	10.5-11.7		Ti6xC%≤0 .70
409L	≤0.03	≤1.0	≤1.0	≤0.04	≤0.03	0.5	10.5-11.7		Ti8xC%≤0 .70
430	≤0.12	≤1.0	≤1.0	≤0.04	≤0.03	1	16.0-18.0		
SS329J4L	≤0.03	≤1.0	≤1.5	≤0.04	≤0.03	5.50-7.50	24.00-26.00	2.5-3.0	



	wenzhoù zheneng Steel maustry Co.,Lia						
٢	15858820108	sales@zhehengsteel.com	e stainless-steelseamlesspipe.com				
No999 .wenzhou airport wenzhou city,zhejiang china							