



ZHEHENG STEEL

Wenzhou Zheheng Steel Industry Co.,Ltd
stainless-steelseamlesspipe.com



Coild Tubing Stainless Steel Coil Tubing 3 / 4 Or 1 / 4 For Heat Exchanger Precision

Our Product Introduction

for more products please visit us on stainless-steelseamlesspipe.com

Basic Information

- Place of Origin: CHINA
- Brand Name: zheheng
- Certification: ISO9001 PED
- Model Number: 19mm
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: In bundles with waterproof material, or wooden crate packing
- Delivery Time: 30 DAYS
- Payment Terms: L/C, T/T, D/A, D/P
- Supply Ability: 50TONS/30DAYS



Product Specification

- Application: Heat Exchanger
- Size: 3/4 ,3/8,1/4,1/2
- Type: Seamless
- Technique: Cold Drawing
- Trade Terms: FOB,CNF,CIF
- Delivery Time: 30 Days
- Highlight: **304 stainless steel coil tubing, stainless steel condenser coil**



More Images



Product Description

coild tubing stainless steel coil tubing 3/4 ,3/8,1/4,1/2, for heat exchanger / cooling pipe coil

zheheng steel is engaged in the production and trade of all kinds of stainless steel coiled tubing ,3/4 ,3/8,1/4,1/2 stainless steel coil tubing,heat exchanger stainless steel coil tubing, we have more than 15 advanced production lines and ET, UT, HT etc advanced test devices for quality inspection and guarantee, our annual export can reach approximate 6000-8000 tons for the main products of seamless and welded stainless steel pipe, pipe fitting and flange. 30% of the entire annual turnover, our production annual capacity is approx. 5000 metric ton.

product description:

Material: 304/304L, 316/316L, 321, etc.

Standard:

ASTM A249 boiler, superheater, heat exchanger and refrigerator are welded austenitic stainless steel pipe.

GB/ t24593-2009 boiler and heat exchangers used austenitic stainless steel welded steel tubes.

GB/ t1271-2008 fluid conveying stainless steel welded steel pipe.

HG/20537.2-92 tube shell heat exchanger is required by austenitic stainless steel welded steel tube.

Outer diameter: 8.0-19.0 mm

Wall thickness: 0.5 1.5 mm

Annealing temperature: 1040-1150c.

Automatic welding visual tracking device: automatically adjust the deviation of welding needle weld and ensure the quality of welding. Online eddy current detector, detect the quality defect of on-line welded pipe.

Water pressure test: pressure 2PM.

Pressure protection test: pressure 2PM, over 5 hours.

Welding method: argon arc welding or plasma welding + argon arc welding.

Product application: boiler, heat exchanger, condenser.

stainless steel coils tubing Applicationed in :

Industrial stainless steel coil: heat exchanger, boiler, oil, chemical, chemical fertilizer, chemical fiber, pharmaceutical, nuclear power, etc.

Liquid stainless steel coil: beverage, beer, milk, water supply system, medical equipment, etc.

The mechanical structure USES stainless steel coil: printing and dyeing, printing, textile machinery, medical equipment, kitchen equipment, automobile and ship accessories, building and decoration, etc.

Stainless steel bright coil pipe: it is welded by the stainless steel strip to reduce the wall, the wall thickness is thick to thin, this process can make the wall thickness even, smooth, and the wall of the wall of the wall is not welded. It is seamless to the naked eye, but the process is welded tube. The process of reducing the wall is accompanied by bright annealing, so that the inner and outer walls will not form the oxide layer, and the inside and outside is bright and beautiful, which is needed for medical products.

stainless steel coil tubing size

Size	OD : 4.76 - 25.4mm
	WT : 0.71 - 2.11mm
	Length : >1000Meters
	4.76 * 0.71mm / 4.76 * 0.89mm / 4.76 * 1.24mm
	6 * 1mm / 6 * 1.5mm
	6.35 * 0.71mm / 6.35 * 0.89mm / 6.35 * 1.24mm / 6.35 * 1.65mm
	7.94 * 0.71mm / 7.94 * 0.89mm / 7.94 * 1.24mm / 7.94 * 1.65mm
	9.53 * 0.71mm / 9.53 * 0.89mm / 9.53 * 1.24mm / 9.43 * 1.65mm
	10 * 1mm / 10 * 1.5mm
	12 * 1mm / 12 * 1.5mm / 12 * 2mm
	12.7 * 0.71mm / 12.7 * 0.89mm / 12.7 * 1.24mm / 12.7 * 1.65mm / 12.7 * 2.11mm
	14 * 1mm / 14 * 1.5mm / 14 * 2mm
	15.88 * 0.89mm / 15.88 * 1.24mm / 15.88 * 1.65mm / 15.88 * 2.11mm
	16 * 1mm / 16 * 1.5mm / 16 * 2mm
	19.05 * 0.89mm / 19.05 * 1.24mm / 19.05 * 1.65mm / 19.05 * 2.11mm
	25.4 * 0.89mm / 25.4 * 1.24mm / 25.4 * 1.65mm / 25.4 * 2.11mm

stainless steel coilded tubing specification:

1/8 ** 0.035 * (1 ~ 3500 m)

1/4 ** (0.035 ~ 0.049) * (1 ~ 1800 m)

1/2 ** 0.049 * (1 ~ 1000 m)

Φ 3 * 0.9 * (1 ~ 3500 m)

Φ 4 * 0.9 * (1 ~ 2500 m)

Φ 6 * 0.9 * (1 ~ 1700 m)

Φ 8 * 1 * (1 ~ 1000 m)

Φ 10 * 1 * (1 ~ 8000 m)

Painted Φ 26 (10 -) (1-2) length (1-800 - m) diameter size according to customer requirements

Materials :201, 202, 304, 304L, 316L, 317L, 321(also customized according to user requirements)

Pressure: 60-100 mpa

Executive standard: ASTM a269-2002.JIS G4305.

GB/T 12770-2002gb/t12771-2002 technical requirements.

Products show:



ZHEHENG STEEL

Wenzhou Zheheng Steel Industry Co.,Ltd



15858820108



sales@zhehengsteel.com



stainless-steelseamlesspipe.com

No999 .wenzhou airport wenzhou city,zhejiang china