



ZHEHENG STEEL

Wenzhou Zheheng Steel Industry Co.,Ltd
stainless-steelseamlesspipe.com

DNV Drilling 25mm Inconel Seamless Pipe

Our Product Introduction

for more products please visit us on stainless-steelseamlesspipe.com

Basic Information

- Place of Origin: CHINA
- Brand Name: zheheng
- Certification: ISO9001 PED
- Model Number: 25mm
- Minimum Order Quantity: Negotiable
- Price: Negotiable
- Packaging Details: In bundles with waterproof material, or wooden crate packing
- Delivery Time: 30 DAYS
- Payment Terms: L/C, T/T, D/A, D/P
- Supply Ability: 50TONS/30DAYS




Product Specification

- Certificates: ABS, DNV, GL, BV, PED 97/23/EC,
- Standard: Astm
- Type: Seamless
- Technique: Cold Rolling
- Application: Drilling
- Material: Inconel Alloy 625
- Highlight: inconel 625 seamless pipe, inconel 625 pipe



More Images



Product Description

Astm alloy inconel 625 / uns n06625 seamless pipe tubing chemical composition / mechanical properties for drilling

zheheng steel produce and supply astm alloy inconel 626 pipes, uns06625 seamless tubing,they have excellent chemical composition,mechanical properties in drilling ,

We warmly welcome friends at home and abroad to contact us for cooperation based on mutual benefits for a bright and successful future.

Features: Inconel alloy 625 has excellent strength at temperatures up to 816°C. At higher temperatures, its strength is generally lower than that of other solid solution strengthened alloys. Inconel alloy 625 has good oxidation resistance at temperatures up to 980°C and shows good resistance to aqueous corrosion, but is relatively moderate compared to other more capable corrosion resistant alloys.

Products description:

Equivalent designations

Characteristics:

1. Good mechanical properties
2. Yield tensile strength
3. Highly resistant to chloride and sulfide stress corrosion cracking
4. Resistant to aqueous corrosion and chloride ion stress corrosion cracking
5. High temperature resistant
6. Age-hardenable with a unique property of slow aging response that permits heating and cooling during annealing without the danger of cracking.
7. Excellent welding characteristics

production specifications :

Specifications	Round bar	Diameter: 3mm~800mm
	Angle bar	Size: 3mm*20mm*20mm~12mm*100mm*100mm
	Square bar	Size: 4mm*4mm~100mm*100mm
	Flat bar	Thickness: 2mm~100mm Width: 10mm~500mm
	Hexagonal	Size: 2mm~100mm

UNS N06625

DIN W. Nr. 2.4856

Inconel 625 Chemical composition:

%	Ni	Cr	Mo	Fe	C	Mn	Si	P	S	Co	Nb+Ta	Al	Ti
min	58	20	8								3.15		
max		23	10	5	0.1	0.5	0.5	0.015	0.015	1	4.15	0.4	0.4

Inconel 625 Physical properties:

Density	8.44 g/cm3
Melting range	1290-1350°C

product show:



ZHEHENG STEEL

Wenzhou Zheheng Steel Industry Co.,Ltd



15858820108



sales@zhehengsteel.com



stainless-steelseamlesspipe.com

