

ASTM Downhole Umbilical Stainless Steel Coil Tubing Plank Welding

Basic Information

Place of Origin: CHINA
Brand Name: zheheng
Certification: ISO9001 PED
Model Number: 25.4mm
Minimum Order Quantity: Negotiable
Price: Negotiable

Packaging Details: In bundles with waterproof material,or

wooden crate packing

• Delivery Time: 30 DAYS

Payment Terms: L/C, T/T, D/A, D/PSupply Ability: 50TONS/30DAYS



Product Specification

• OD: 25.4MM

• WT: 0.89MM,1.24MM,1.65MM,2.11MM

Standard: ASTMApplication: Industry

• Steel Grade: Super Duplex Stainless Steel Coil

Welding Line Type: SeamlessSurface: Bright

• Product Name: Stainless Steel Tubing, stainless Steel Coil

Tube

• Keyword: Stainless Steel Pipe, Stainless Steel Coil

Lubing

Color: Natural Color, Silver White Stainless Steel

Pipe

• Highlight: Umbilical Stainless Steel Coil Tubing,

ASTM Stainless Steel Coil Tubing, Downhole Stainless Steel Coil Tubing



More Images





Product Description

ASTM Downhole Umbilical Stainless Steel Coil Tubing Plank Welding

Basic composition and development status of deep sea umbilical cable. The basic requirements and main components of umbilical cable inner tube production line, namely super duplex stainless steel coil production line, are briefly described. The structure and function of the main equipment of the production line are analyzed, such as tube - tube full position butt welding device, polishing device, X-ray plate digital imaging detection device, rewinding device and hydraulic test device. The trial production of 14.7mm ×1 mm S32750(2507) super double-phase stainless coil has been carried out by using this production line. The test results show that the mechanical properties of the trial production coil completely meet the requirements of ISO 13628-5 -- 2009 and other relevant standards, and the production line can meet the needs of actual production.

Product name:	Precision cold-drawn stainless steel bright seamless coil tubing (whole roll pure seamless)
Production process:	First cold rolling, then cold drawing and coiling.
Surface treatment:	Vacuum bright annealing (vacuum bright annealing process, the inner and outer surface of the stainless steel tube will not contact with oxygen, no
	oxide skin, so that the inner and outer surface of the stainless steel coil is cleaner, brighter and more delicate)
Delivery state:	soft state (HRB≤90)
Material of coil:	304/ 304L / 321/ 317L / 2205/ 2507
Production standard:	ASTM(ASME)SA/ A312 / A213 / A269,DIN, GB,JIS.
Coil tubing specification:	OD Φ 4mm-x 31.8mm, wall thickness (WT):0.7-2.11mm.
Tolerance range:	Outside diameter: ±0.1mm, wall thickness: ±10%.
Coil length:	
1.1:	According to the difference of outer diameter and wall thickness, the production weight of a seamless coil tubing reaches about 120KG.
1.2:	Please note that the longer the length of seamless coil is, the more difficult it is to produce, and the higher the price will be.
1.3:	The length of the stainless steel coil tubing according to the external diameter and wall thickness of the demand, using the stainless steel pipe theory calculation formula conversion.
1.4:	Solemnly declare: the whole reel seamless coil has no welding point.
1.5:	According to the demand, can also be used with a number of stainless steel seamless coil butt welding into a few thousand meters above the super-long stainless steel coil tubing.
Finished product inspection:	Hydraulic test (10Mpa - 35Mpa)/ air pressure test/eddy current flaw detection test.
Coding identification:	According to customer requirements.
Packing method:	Using woven bags or plywood boxes, plywood spools, convenient transportation and storage; The finished stainless steel coil will be wrapped into roll of packing or wrapped in wooden shaft packing, sea, land transportation, air transportation are very convenient, reduce transportation costs and convenient customer inventory storage.
Delivery time:	
2.1:	T/T settlement can be settled with KG price and rice price.
2.2:	The production cycle of stainless steel seamless coil with a single roll weight less than 30KG is about 25-30 days.
2.3:	Stainless steel seamless coil tubing single volume weight 30Kg-50Kg production cycle in about 35-45 days.
2.4:	Single roll weight of stainless steel seamless coil tubing is 50Kg-120Kg. The production cycle is about 50-60 days.
Product advantages:	Stainless steel bright coil tubing in use can be cut according to the required length requirements, bending, reduce waste, reduce costs, especially in the transmission pipeline installation to save the installation of joints, improve ety performance. Seamless coils are a good choice to reduce leakage risk in hydraulic systems. In the process of installation, the use of joints is greatly reduced, and the ety of the whole pipeline system is completely improved. Enhance the security of system operation.
Scope of application:	Stainless steel coil tubing is widely used in oil drilling, shipbuilding, aerospace and petrochemical refining equipment, spiral around the pipe heat exchanger, the residual wound tube heat exchanger and cold treatment, chemical industry pipeline, fluid pipe, steam heat preservation pipe, stainless steel heating coil (heating coil pipe), high pressure fluid pipes, stainless steel heat preservation heat insulation pipe line, Anticorrosive stainless steel pipes and cables protected by PVC sheath, umbilical cables and other industries.

product show:





Wenzhou Zheheng Steel Industry Co.,Ltd

15858820108

sales@zhehengsteel.com



stainless-steelseamlesspipe.com

No999 .wenzhou airport wenzhou city,zhejiang china