



ZHEHENG STEEL

Wenzhou Zheheng Steel Industry Co.,Ltd
stainless-steelseamlesspipe.com



Schedule 10s Welded Stainless Steel Seamless Pipe DIN1.4306 1/8"

Basic Information

- Place of Origin: Wenzhou,China
- Brand Name: Zheheng
- Certification: ISO9001,ISO14001, TS16949
- Model Number: DIN 1.4306
- Minimum Order Quantity: MOQ 1Ton
- Packaging Details: In wooded cases or pallets,or as for clients requirement
- Delivery Time: 7-15 working days after receiving payment
- Payment Terms: L/C, D/P, T/T, Western Union
- Supply Ability: 1000 Ton/Tons per Month



Product Specification

- Thickness: 1mm-150mm(SCH10-XXS) Or As Required
- OD: 1/8"-80
- Section Shape: Round,Square,rectangular
- Surface Finish: Polishing, Hair Line,Pickling
- Price Terms: FOB,CIF,CFR,EXW
- Length: 1000-12000mm
- Application Fields: Marine,Construction Industry
- Technique: Cold Drawn Or Hot Rolled
- Highlight: **Seamless Stainless Steel Welded Pipe,
Schedule 10s Seamless Pipe,
DIN1.4306 Stainless Steel Pipe**



Our Product Introduction

for more products please visit us on stainless-steelseamlesspipe.com

Product Description

Characteristic

DIN1.4306 belong to low carbon steel grade, Rather than its demonstrates excellent corrosion resistance For severely corrosive environments, the lower content of Type SUS304L is preferred because of its greater immunity to intergranular corrosion. DIN 1.4306 stainless steel include in the Power Genration Industry ,Chemical Industry ,Oil&Gas Industry, Petrochemical Industry.

Specification

Ends	Plain end
Standard	EN
Delivery time	within 45 -60 days.
Payment Terms	40% prepayment Balance before lodaing.
Shipping Terms	FOB NINGBO, after the inspection of goods at supplier's warehouse
Package	Standard export seaworthy package, or as required.

1.4306 stainless pipe Chemical Composition

Grade	C ≤	Si ≤	Mn ≤	P ≤	S ≤	Ni ≤	Cr ≤	N ≤
DIN1.4306	0.030	1.00	0.80	0.040	0.015	10.00-12.00	18.00-19.00	0.11

Mechanical propertoes

Material	Tensile strength(Mpa)	Yield point(Mpa)	Elongation(%) Longitudinal	Elongation(%) transverse
1.4306	480-680	180	40	35

Product Testing

Coating Thk Test
Geometry inspection
Ultrasonic Inspection
Nondestructive Testing
Hydrostatic Testing

Package Process

- 1.with plastic cap to protect both ends
- 2.weaving bag wrapped outside the pipe
- 3.then pack into wooden case.

Image



ZHEHENG STEEL

Wenzhou Zheheng Steel Industry Co.,Ltd

