

BS 321S20 Stainless Steel Pipe TP321 Bright Annealed With Circular Cross Section

Basic Information

Place of Origin: Wenzhou, China
Brand Name: Zheheng
Certification: ISO9001

Model Number: BS 321S20Minimum Order Quantity: MOQ500kg

• Packaging Details: In wooded cases or pallets,or as for clients

requirement

Delivery Time: 7-15 working days after receiving payment

Payment Terms: L/C, D/P, T/T, Western Union
 Supply Ability: 1000 Ton/Tons per Month



Product Specification

Other Name: DIN 1.4541,TP321
 Thickness: 0.6-12.7mm
 Size: 6NB-1200NB
 OD: 1/8"-12"NPS

• Shape: Round, Square, Rectangle

• Technical: Cold Drawn, Bright Annealed, Annealed And

Pickled, Polished

Price Terms: FOB,CIF,CFR,EXW

• Length: 800mm,2000mm,5800mm,6000mm,12000mr

As Required.

• Highlight: BS 321S20 Stainless Steel Pipe,

Bright Annealed Stainless Pipe, Stainless Steel Pipe TP321



Product Description

BS 321S20 Stainless Steel Pipe of Specification

SUS321 Stainless Steel Pipe is stabilized by titanium and designed with a chemical composition of 17 to 19% chromium with 9 to 12% of nickel. These pipes show enhanced corrosion and oxidation resistance across stress-induced environments.

Chemical Composition

G	RADE	UNS	С	Mn	Р	S	Si	Cr	Ni	Мо	Ti	Nb	N
32	21S20	S3210	0.08	2.0	0.045	0.030	1.0	17.0-19.0	9.0-12.0	-	-	-	0.10

BS 321S20 Mechanical Properties

ASTM A312 Stainless Steel Pipes Mechanical Properties									
Material	Heat Treatment		Tensile Strength Ksi (MPa), Min.		Elongation %, Min				
321S20	Solution	1900(1040)	75(515)	30(205)	35				

Application

Steel pipes are widely used in interior decoration, factories and various environments.

Packaging

Plastic caps plugged at the two sides of pipe ends.

Should be avoided by the steel strapping and transport damage.

Bundled signs should be uniform and consistent.

Our packing can meet any needs of the customers.

Image





Wenzhou Zheheng Steel Industry Co.,Ltd



15858820108



sales@zhehengsteel.com



stainless-steelseamlesspipe.com

No999 .wenzhou airport wenzhou city,zhejiang china