



ZHEHENG STEEL

Wenzhou Zheheng Steel Industry Co.,Ltd
stainless-steelseamlesspipe.com

Hot Rolling SS Seamless Tube UNS S31703 Thickness 9.0mm 3 Inch

Our Product Introduction

for more products please visit us on stainless-steelseamlesspipe.com

Basic Information

- Place of Origin: Wenzhou, China
- Brand Name: Zheheng
- Certification: ISO9001
- Model Number: UNS S31703
- Minimum Order Quantity: MOQ500kg
- Packaging Details: In wooded cases or pallets, or as for clients requirement
- Delivery Time: 7-15 working days after receiving payment
- Payment Terms: L/C, D/P, T/T, Western Union
- Supply Ability: 1000 Ton/Tons per Month



Product Specification

- Common Name: 00Cr19Ni13Mo3, SUS317L
- Port: Ningbo
- OD: 200mm
- Section Shape: Round
- Package: Seaworthy Standard Package
- Price Terms: FOB, CIF, CFR, EXW
- Length: 1-12m
- Technique: Cold Drawn Or Hot Rolled
- Wall Thickness: 0.5~100 Mm, Sizes Can Be Customized
- Highlight: **Hot Rolling SS Seamless Tube,
UNS S31703 Seamless Tube,
9.0mm Seamless Stainless Pipe**



Product Description

Characteristic

UNS S31703 is a low carbon version of grade 317 stainless steel. It can produce stronger welds due to the low carbon content. It has higher ductility, stress corrosion resistance, compressive strength and high temperature resistance

Grade S31703 stainless steel is widely used in the following applications:

- 1) Oil and gas industry equipment;
- 2) Offshore platforms, heat exchangers, underwater equipment, firefighting equipment;
- 3) Chemical processing industry, utensils and pipeline industry;
- 4) Desalting, high pressure RO equipment and submarine pipelines;
- 5) Energy industry such as power plant desulfurization and denitration FGD system, industrial scrubbing system, absorption tower;
- 6) Mechanical parts that require high strength, corrosion resistant and anti-wear performance;

Chemical Composition

N	0.10
C	0.03
Mn	2
P	0.045
S	0.03
Si	0.75
Cr	18.0-20.0
Ni	11-15
Mo	3.0-4.0

Mechanical Properties

Material	Ultimate Tensile Strength(Mpa)	0.2%Yield Strength (Mpa)	%Elongation in2"	Rockwell B Hardness
UNS S31703	515	205	40	95

Product Testing

Hydrostatic test
Flaw detection test
Lab test

Package Process


- 1.with plastic cap to protect both ends
- 2.weaving bag wrapped outside the pipe
- 3.then pack into wooden case.

Image





 15858820108

 sales@zhehengsteel.com

 stainless-steelseamlesspipe.com

No999 .wenzhou airport wenzhou city,zhejiang china