

EN 1.4558 Seamless Stainless Steel Tube Pipe Sch80S Intended For Pipelines

Basic Information

Place of Origin: CHINA

Brand Name: zheheng steel
Certification: iso9001
Model Number: 88.9mm
Minimum Order Quantity: Negotiable
Price: Negotiable

Packaging Details: In bundles with waterproof material,or

wooden crate packing

• Delivery Time: 30 DAYS

Payment Terms: L/C, T/T, D/A, D/PSupply Ability: 50TONS/30DAYS



Product Specification

• Material: 1.4558

• Standard: ASTM, GB, JIS, DIN, EN, AISI

Shape: Sch80s
Technique: Cold-drawn
APPLICATION: Chemical
Package: Woven Packing
OD: 6-830mm

Highlight: Seamless Stainless Steel Tube Pipe,

EN 1.4558 Stainless Steel Tube, 830mm Stainless Steel Pipe



Product Description

EN 1.4558 (X2NiCrAITi32-20) Stainless Steel Tube Sch80S intended for pipelines

Introduction to products:

EN 1.4558 stainless steel is a superaustenitic (highly alloyed) stainless steel formulated for primary forming into wrought products. Cited properties are appropriate for the solution annealed (AT) condition. 1.4558 is the EN numeric designation for this material. X2NiCrAlTi32-20 is the EN chemical designation.

It has a very low tensile strength among wrought superaustenitic stainless steels. In addition, it has a moderately low base cost and a moderately low embodied energy.

APPLICATIONS:

The 1.4558 grade is used in the chemical industry equipment manufacturing nitric acid and derivatives, salts and fertilizers. Also used in cryotechnics, in the pharmaceutical industry, in the food industry - in food processing plants, dairies, sugar factories, breweries, in the fuel industry, i.e. in refineries and petrochemical plants.

Steel intended for pipelines, autoclaves, transport tanks, heat exchangers, absorption towers, pumps, coolers, and reactors.

Chemical Composition of 1.4550

Chemical Composition, %											
(Regio	Stand ard	Steel Grade (Steel Number)		C, ≤	Si, ≤	Mn, ≤	P, ≤	S, ≤	Cr	Ni	Nb
Europ ean Union	EN 10216	X2NiCrAlTi32	MIN						17	9	10xC to 1.00
		(1.4558)	MAX	0.08	1	2	0.04	0.015	19	12	

Description for our production range:

Name: Stainless Steel seamless Pipe

Standard :EN10216-5, EN10216-2, DIN 17456, DIN 17458, ASTM A312,

A213, A269, A511, A789, A790 ETC, GOST 9941, GOST 5632,

JIS G3459, JIS G3463,GB/T14975,GB/T14975, GB13296, GB5310, GB9948

Material Grade:

1.4558

Diameter :OD: 6-830mm **W.T:** 0.6mm - 60mm

Length: Up to 13 meter or as customers' request

Tolerance : According to the Standard.

Surface:

Natural Color of annealing & pickling, 180G, 320G, 400G Satin / Hairline

400G, 500G, 600G or 800G Mirror finish

Test:

UT, ET, HT, RT, ect, and others according to the standard,

or as the requests of the customer

our products packing:



Tensile Requirements - Stainless Steel 310S/310H:

Tensile Strength (KSI): 75 Yield Strength (KSI): 30

Notes:

 $\begin{array}{l} 10\text{-}6\text{-}K\text{-}1=10\text{-}6\text{/}K\\ 1~\Omega\text{-}mm^2\text{/}m=1~\mu\Omega\text{-}m\\ 1~g\text{/}cm3=1~kg\text{/}dm3=1000~kg\text{/}m3\\ 1~GPa=1~kN\text{/}mm2\\ 1~MPa=1~N\text{/}mm2 \end{array}$

other supplement:

- 1.A999/A999M: Each pipe shall be subjected to the nondestructive electric test or the hydrostatic test, the pipe of test to be used shall be at the option of the mfg, unless otherwise specified in the PO.
- 2. The Pipe lengths: Unless otherwise agreed upon, all size from NPS 1/8" TO AND INCLUDING nps 8 are available in a length up to 24ft with the permitted range of 15 to 24 ft. Short length are acceptable and the number and min, length shall be agreed upon between mfg and purchaser.
- 3. The finished pipe shall be reasonably straight and shall have workmanlike finish, Removal of imperfections by grinding is permitted, provided the W.T are not decreased to the less than the permitted in Section 9 of Specification A999/A999M
- 4. Butt Weld End: According to ANSI B 16.25
- 5. Pipe Marking: Specified in A999/999M, include "Logo+Standard+SIZE+Heat No.+Lot No.+H.T/E.T/U.T"
- 6. Packing: Each Pipe end is protected by Plastic cap. Then packed by Anti-rust steel strip, The outside of the bundle is plastic woven bag, or Plastic film.
- 7. Packing Mark: SIZE + STEEL GRADE+ QTY OF PIECE/WEIGHT/METRE.
- 8.MTC: BWSS Official Original MTC paper will be supplied for each order.



Wenzhou Zheheng Steel Industry Co.,Ltd

15858820108

sales@zhehengsteel.com

stainless-steelseamlesspipe.com

No999 .wenzhou airport wenzhou city,zhejiang china