CHINA

iso9001

88.9mm

Negotiable

50TONS/30DAYS

In bundles with waterproof material,or

zheheng steel

Sch80S Stainless Steel Pipe Tube ASTM TP201 S20100 In Petroleum Industry

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity: Negotiable
- Price:
- Packaging Details:
- wooden crate packing • Delivery Time: 30 DAYS L/C, T/T, D/A, D/P
- Payment Terms:

• Supply Ability:

Product Specification

- Material:
- Standard: • Shape:

• Technique: • APPLICATION:

• Package: • OD:

• Highlight:

- TP201 ASTM, GB, JIS, DIN, EN, AISI Sch80s Cold-drawn Chemical Woven Packing
- 6-830mm
- Sch80S Stainless Steel Seamless Pipe, Petroleum Industry Stainless Steel Pipe, **TP201 Stainless Steel Pipe**



Our Product Introduction

Sch80S Stainless Steel Pipe Tube ASTM TP201 S20100 used in petroleum industry

Introduction to products:

Cr-Ni Austenitic stainless steels 201 tubing is a lower-cost alternative to the SS304. It has wider applications, has been used for handrails, decorates pipe, instruments or other places where need corrosion resistance and lower costs.

Application:

ASTM A554 TP201 stainless steel pipes are generally used in petroleum industry, pharmaceutical industry, food industry, aviation and aerospace industry, boiler and heat exchanger industry, architectural decoration industry, fluid transports and so on.

Chemical composition

	≤0.15
	≤1.00
	5.50 7.50
	≤0.060
	≤0.030
	3.50 5.50
Cr	16.00 18.00
Лο	/
Cu	/
1	≤0.25

N N C

Description for our production range:

Name :Stainless Steel seamless Pipe Standard : EN10216-5 , EN10216-2, DIN 17456 , DIN 17458, ASTM A312, A213, A269, A511, A789, A790 ETC, GOST 9941, GOST 5632, JIS G3459, JIS G3463, GB/T14975, GB/T14975, GB13296, GB5310, GB9948 Material Grade : 1 4571 Diameter :OD: 6-830mm W.T: 0.6mm - 60mm Length : Up to 13 meter or as customers' request Tolerance : According to the Standard. Surface : Natural Color of annealing & pickling, 180G, 320G, 400G Satin / Hairline 400G, 500G, 600G or 800G Mirror finish Test : UT, ET, HT, RT, ect, and others according to the standard, or as the requests of the customer

our products packing:



Notes:

10-6·K-1 = 10-6/K	
$1 \Omega \cdot mm^2/m = 1 \mu \Omega \cdot m$	
1 g/cm3 = 1 kg/dm3 = 1000) kg/m3
1 GPa = 1 kN/mm2	-
1 MPa = 1 N/mm2	

other supplement:

1.A999/A999M: Each pipe shall be subjected to the nondestructive electric test or the hydrostatic test, the pipe of test to be used shall be at the option of the mfg, unless otherwise specified in the PO.

2. The Pipe lengths : Unless otherwise agreed upon, all size from NPS 1/8" TO AND INCLUDING nps 8 are available in a length up to 24ft with the permitted range of 15 to 24 ft. Short length are acceptable and the number and min, length shall be agreed upon between mfg and purchaser.

3. The finished pipe shall be reasonably straight and shall have workmanlike finish, Removal of imperfections by grinding is permitted, provided the W.T are not decreased to the less than the permitted in Section 9 of Specification A999/A999M 4. Butt Weld End: According to ANSI B 16.25

5. Pipe Marking: Specified in A999/999M, include "Logo+Standard+SIZE+Heat No.+Lot No.+H.T/E.T/U.T"

6. Packing: Each Pipe end is protected by Plastic cap. Then packed by Anti-rust steel strip, The outside of the bundle is plastic woven bag, or Plastic film.

7. Packing Mark: SIZE + STEEL GRADE+ QTY OF PIECE/WEIGHT/METRE.

8.MTC: BWSS Official Original MTC paper will be supplied for each order.

